

# 12FH500

12" - 500 W - 96 dB - 16 Ohm



## NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	284 mm (11.18 in)
Depth	155.75 mm (6.13 in)
Flange and Gasket Thickness	12.45 mm (0.49 in)
<b>Net Weight</b>	<b>3.9 Kg (8.6 lb)</b>
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	4.7 Kg (10.4 lb)

## PART NUMBER

Push Terminals - 16 Ohm Version	03004123
---------------------------------	----------

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth)/3$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	16 Ohm
Minimum Impedance	14.4 Ohm
AES Power Handling (1)	500 W
<b>Maximum Power Handling (2)</b>	<b>1000 W</b>
<b>Sensitivity (1W/1m)</b>	<b>96 dB</b>
Frequency Range	45-4000 Hz
<b>Voice Coil Diameter</b>	<b>77 mm (3 in)</b>
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	18 mm (0.71 in)
<b>Magnetic Gap Depth</b>	<b>10.5 mm (0.41 in)</b>
Flux Density	1.2 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	M-Roll
NET Air Volume filled by Loudspeaker	2.3 dm <sup>3</sup> (0.081 ft <sup>3</sup> )
Spider Profile	1x variable height waves

## THIELE & SMALL PARAMETERS

Fs	48 Hz
Re	12.8 Ohm
Qes	0.38
Qms	11
Qts	0.36
Vas	66.6 dm <sup>3</sup> (2.35 ft <sup>3</sup> )
Sd	487 cm <sup>2</sup> (75.49 in <sup>2</sup> )
Xmax (4)	7.25 mm
Xdamage (5)	16 mm
Mms	55.5 g
Bl	23.8 N/A
Le	1.2 mH
Mmd	49.3 g
Cms	0.21 mm/N
Rms	1.52 Kg/s
Eta Zero	1.93 %
EBP	126 Hz

