

18HP1022



18" - 1000 W - 98 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Overall Diameter	460 mm (18.11 in)
Bolt Circle Diameter	440 mm (17.32 in)
Baffle Cutout Diameter	422 mm (16.61 in)
Depth	202 mm (7.95 in)
Flange and Gasket Thickness	14 mm (0.55 in)
Net Weight	6.6 Kg (14.6 lb)
Shipping Box (Single Carton Box)	503 x 500 x 258 mm (19.8 x 19.7 x 10.2 in)
Shipping Weight	7.8 Kg (17.2 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	04604159
--------------------------------	----------

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.5 Ohm
AES Power Handling (1)	1000 W
Maximum Power Handling (2)	2000 W
Sensitivity (1W/1m)	98 dB
Frequency Range	35-1600 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	23 mm (0.91 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.3 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	5.8 dm ³ (0.205 ft ³)
Spider Profile	2x non-adjacent symmetrical constant height waves

THIELE & SMALL PARAMETERS

Fs	35 Hz
Re	5.4 Ohm
Qes	0.31
Qms	14.4
Qts	0.3
Vas	179 dm ³ (6.32 ft ³)
Sd	1124 cm ² (174.22 in ²)
Xmax (4)	9.50 mm
Xdamage (5)	17.5 mm
Mms	207.0 g
Bl	28 N/A
Le	1.75 mH
Mmd	185.7 g
Cms	0.10 mm/N
Rms	3.67 Kg/s
Eta Zero	2.43 %
EBP	113 Hz

