

4FE35



4" - 30 W - 91 dB - 4 Ohm

NOMINAL SPECIFICATIONS

| | |
|---|--|
| Nominal Diameter | 100 mm (4 in) |
| Overall Diameter | 129.85/100.5 mm (5.11/3.96 in) |
| Bolt Circle Diameter | 115.26 mm (4.54 in) |
| Baffle Cutout Diameter | 91.5 mm (3.60 in) |
| Depth | 49.8 mm (1.96 in) |
| Flange and Gasket Thickness | 7.2 mm (0.28 in) |
| Net Weight | 570 g (1.3 lb) |
| Shipping Box (Single Carton Box - 8 units) | 225 x 225 x 150 mm (8.9 x 8.9 x 5.9 in) |
| Shipping Weight (8 units) | 5 Kg (11.0 lb) |

PART NUMBER

| | |
|----------------------------------|----------|
| Faston Terminals - 4 Ohm Version | 01004109 |
|----------------------------------|----------|

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) NBR (Rubber)
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

| | |
|--------------------------------------|--|
| Nominal Impedance | 4 Ohm |
| Minimum Impedance | 3.7 Ohm |
| AES Power Handling (1) | 30 W |
| Maximum Power Handling (2) | 60 W |
| Sensitivity (1W/1m) | 91 dB |
| Frequency Range | 90-20000 Hz |
| Voice Coil Diameter | 19 mm (0.75 in) |
| Winding Material | Al |
| Former Material | Kapton |
| Winding Depth | 4.8 mm (0.19 in) |
| Magnetic Gap Depth | 4 mm (0.16 in) |
| Flux Density | 1.1 T |
| Magnet | Ferrite Ring |
| Basket Material | Steel |
| Demodulation | Copper Cap |
| Cone Surround (3) | Half Roll |
| NET Air Volume filled by Loudspeaker | 0.150 dm ³ (0.005 ft ³) |
| Spider Profile | 1x constant height waves |

THIELE & SMALL PARAMETERS

| | |
|-------------|--|
| Fs | 100 Hz |
| Re | 3.3 Ohm |
| Qes | 0.92 |
| Qms | 3.9 |
| Qts | 0.73 |
| Vas | 2.12 dm ³ (0.07 ft ³) |
| Sd | 48 cm ² (7.44 in ²) |
| Xmax (4) | 1.73 mm |
| Xdamage (5) | 6.8 mm |
| Mms | 3.9 g |
| Bl | 3 N/A |
| Le | 0.04 mH |
| Mmd | 4.1 g |
| Cms | 0.65 mm/N |
| Rms | 0.62 Kg/s |
| Eta Zero | 0.23 % |
| EBP | 109 Hz |

