

8PR155

8" - 200 W - 97 dB - 8 Ohm



NOMINAL SPECIFICATIONS

| | |
|-------------------------------------|--|
| Nominal Diameter | 200 mm (8 in) |
| Overall Diameter | 223.7/207.9 mm (8.81/8.18 in) |
| Bolt Circle Diameter | 210 mm (8.27 in) |
| Baffle Cutout Diameter | 183 mm (7.20 in) |
| Depth | 98.5 mm (3.88 in) |
| Flange and Gasket Thickness | 10.8 mm (0.43 in) |
| Net Weight | 4.3 Kg (9.5 lb) |
| Shipping Box (Single Carton Box) | 235 x 235 x 155 mm (9.3 x 9.3 x 6.1 in) |
| Shipping Weight | 4.6 Kg (10.1 lb) |

PART NUMBER

| | |
|----------------------------------|----------|
| Faston Terminals - 8 Ohm Version | 02004172 |
|----------------------------------|----------|

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

| | |
|--------------------------------------|---|
| Nominal Impedance | 8 Ohm |
| Minimum Impedance | 6.3 Ohm |
| AES Power Handling (1) | 200 W |
| Maximum Power Handling (2) | 400 W |
| Sensitivity (1W/1m) | 97 dB |
| Frequency Range | 80-6300 Hz |
| Voice Coil Diameter | 52 mm (2 in) |
| Winding Material | Al |
| Former Material | Glass Fiber |
| Winding Depth | 9.8 mm (0.39 in) |
| Magnetic Gap Depth | 8 mm (0.31 in) |
| Flux Density | 1.3 T |
| Magnet | Ferrite Ring |
| Basket Material | Aluminum |
| Demodulation | Aluminum Ring |
| Cone Surround (3) | Triple Roll |
| NET Air Volume filled by Loudspeaker | 1.06 dm ³ (0.037 ft ³) |
| Spider Profile | 1x variable height waves |

THIELE & SMALL PARAMETERS

| | |
|-------------|--|
| Fs | 85 Hz |
| Re | 5.3 Ohm |
| Qes | 0.39 |
| Qms | 8.8 |
| Qts | 0.37 |
| Vas | 8.7 dm ³ (0.31 ft ³) |
| Sd | 207 cm ² (32.09 in ²) |
| Xmax (4) | 3.57 mm |
| Xdamage (5) | 10.65 mm |
| Mms | 24.5 g |
| Bl | 13.4 N/A |
| Le | 0.41 mH |
| Mmd | 22.8 g |
| Cms | 0.14 mm/N |
| Rms | 1.48 Kg/s |
| Eta Zero | 1.35 % |
| EBP | 218 Hz |

